


ARCTIC FLASH

SYNTHETIC FLASHING



HomeGuard™ ARCTIC FLASH synthetic flashing products are the smart choice to help prevent air and water from entering around window and door openings. They are designed for above grade use, are easily installed, and will adhere to most substrates.

HomeGuard ARCTIC FLASH synthetic flashing is a high tack, high performance self-adhered window and door flashing tape designed with a wide application temperature range from -29°C to extreme heat without requiring primer or mechanical fasteners. Available in 4", 6", 9" and 12" x 75' rolls.

- Peel-n-stick -- easy installation
- Can be applied down to **-29° C**
- 6 month UV exposure
- High tack - **no primer required**
- Excellent air & moisture barrier properties
- Compatible with sealants & caulking
- Self-seals around properly installed fasteners
- No VOCs, HFCCs, or CFCs
- Split release liner
- Made in the USA

Technical Data for **HomeGuard™ ARCTIC FLASH** synthetic flashing

	HomeGuard Arctic Flash	3M 8067/3015 All Weather Flash	Protecto Super Stick	Resisto Red Zone
Application Limit	-29C	-18C	-28C	-10C
Primer Required	No	No	No	Yes
Low Temp Flex	Pass	Pass	Pass	Pass
UV Resistance	6 months	6 months	12 months	3 months
Self Sealing	Yes	Yes	Yes	Yes
Split Release Liner	Yes	Yes	Yes	No
Compatible with all materials	Yes	Yes	Yes	No
Code Compliance	AAMA 711-07	AAMA 711-05	AAMA 711-05	?

Installation

